

Making our world more productive

Safety advice. Compressed gases

Safety Data Sheet

CORGON® 552 Issue Date: 01 Aug 2014 Revision No: 01

Revision Date: 01-January-2022

Version: 01

1. PRODUCT AND COMPANY IDENTIFICATION

Trade Name CORGON® 5S2 UN-No UN 1956

Recommended Use Compressed Gas for Gas Metal Arc Welding

Manufacturer's Registered Office Oxygen House,

P-43 Taratala Road, Kolkata - 700088

Telephone Number (+91 33) 66021600

24 Hour Emergency Contact No: (+91) 9831851034

Linde India Limited

Oxygen House, P-43 Taratala Road, Kolkata-700 088

Phone (+91 33) 66021600

2. HAZARDS IDENTIFICATION

WARNING! EMERGENCY OVERVIEW

Simple asphyxiant - this product does not contain oxygen and may cause suffocation if released in confined area. Maintain oxygen levels above 19.5%

High pressure compressed gas
Keep at temperatures below 520C / 1250F

Physical State Compressed gas

Odor Odorless

Potential Health Effects

Principal Routes of Exposure Inhalation.

Appearance Colorless

Acute Toxicity

Inhalation Simple asphyxiant. May cause suffocation by displacing the oxygen in the air. Exposure to an oxygen-

deficient atmosphere (<19.5%) may cause dizziness, drowsiness, nausea, vomiting, excess

salivation, diminished mental alertness, loss of consciousness, and death. Exposure to atmospheres containing 8-10% or less oxygen will bring about unconsciousness without warning and so quickly that the individuals cannot help or protect themselves. Lack of sufficient oxygen may cause serious

injury or death.

Depending on concentration and duration of exposure to carbon dioxide may cause increased respiration, headache, mild narcotic effects, increased blood pressure and pulse, and asphyxiation. Symptoms of overexposure become more apparent when atmospheric oxygen is decreased to 15-17%.

Eyes None known. Contact with rapidly expanding gas near the point of release may cause severe harm.

Skin None known.

Skin Absorption Hazard No known hazard by skin absorption.

Ingestion None known.

Chronic Effects Chronic harmful effects are not known from repeated inhalation of concentrations below PEL/TLV.

Aggravated Medical Conditions Respiratory disorders.

Environmental Hazard See Section 12 for additional Ecological Information.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Volume %	Chemical Formula
Argon	7440-37-1	93	Ar
Carbon dioxide	124-38-9	5	CO ₂
Oxygen	7782-44-7	2	0,

4. FIRST AID MEASURES

Eye Contact None under normal use. Get medical attention if symptoms occur.

Skin Contact None under normal use. Get medical attention if symptoms occur.

Inhalation PROMPT MEDICAL ATTENTION IS MANDATORY IN ALL CASES OF INHALATION OVEREXPOSURE. RESCUE

PERSONNEL SHOULD BE EQUIPPED WITH SELF-CONTAINED BREATHING APPARATUS (SCBA).

Conscious inhalation

victims should be assisted to an uncontaminated area and inhale fresh air. If breathing is difficult, Administer oxygen under medical supervision / trained personnel supervision. Unconscious persons should be moved to an uncontaminated area and, as necessary, given artificial resuscitation and supplemental oxygen. Treatment should be symptomatic and supportive.

Linde India Limited
Oxygen House, P-43 Taratala Road, Kolkata-700 088
Phone (+91 33) 66021600

Ingestion None under normal use. Get medical attention if symptoms occur.

5. FIRE-FIGHTING MEASURES

Flammable Properties Not flammable. Does not support combustion

Suitable Extinguishing MediaUse extinguishing agent suitable for the type of surrounding fire.

Explosion Data

Sensitivity to Mechanical Impact None

Sensitivity to Static Discharge None

Specific Hazards Arising from the

Chemical

Cylinders may rupture under extreme heat. Continue to cool fire-exposed cylinders until flames are

extinguished. Damaged cylinders should be handled only by specialists.

Protective Equipment and Precautions for Firefighters

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Ensure adequate ventilation. Evacuate personnel to safe areas. Use personal protective equipment.

Monitor oxygen level.

Environmental Precautions Prevent the spreading of vapors through sewers, ventilation systems, and confined areas.

Methods for Containment Stop the flow of gas or remove the cylinder to an outdoor location if this can be done without risk. If a

leak is in the container or container valve, contact the appropriate emergency telephone number in

Section 1 or call your closest Linde location.

Methods for Cleaning Up Return cylinder to Linde India Ltd.

Other Information Ventilate the area.

7. HANDLING AND STORAGE

Handling Use only in ventilated areas. Never attempt to lift a cylinder by its valve protection cap.

Protect cylinders from physical damage; do not drag, roll, slide or drop. When moving cylinders, even for a short distance, use a trolley designed to transport cylinders. Use equipment rated for cylinder pressure. Use a backflow preventive device in the piping. Never insert an object (e.g., wrench, screwdriver, pry bar, etc.) into valve cap openings. Doing so may damage the valve, causing a leak to occur.

Close valve after each use and when empty. If a user experiences any difficulty operating the cylinder valve discontinue use and contact the supplier.

Never put cylinders into trunks of cars or unventilated areas of passenger vehicles. Never attempt to refill a compressed gas cylinder without the owner's written consent. Never strike an arc on a compressed gas cylinder or make a cylinder a part of an electrical circuit.

For additional recommendations consult rule number 20 of the Gas Cylinders, Rules, 2016.

Storage Protect from physical damage. Cylinders should be stored upright with a valve protection cap in place

and firmly secured to prevent falling. Store in a cool, dry, well-ventilated area of non-combustible construction away from high traffic areas and emergency exits. Keep at temperatures below 52°C /

125°F.

Full and empty cylinders should be segregated. Use a "First In-First Out" (FIFO) inventory system to prevent full cylinders from being stored for excessive periods of time. Always store and handle compressed gas cylinders in accordance with rule number 21 of the Gas Cylinders, Rules, 2016.

Disclaimer: Linde plc has no control whatsoever as regards performance or non-performance, misinterpretation, proper or improper use of any information or suggestions contained in this instruction by any person or entity and Linde plc expressly disclaims any liability in connection thereto.

Linde India Limited
Formerly known as BOC India Limited
Oxygen House, P-43 Taratala Road, Kolkata-700 088
Phone (+91 33) 66021600

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSHIDLH
Carbon dioxide 124-38-9	STEL = 30000 ppm TWA: 5000 ppm	30000 ppm	IDLH: 40000 ppm TWA: 5000 ppm TWA: 9000 mg/m ³ STEL: 54000 mg/m ³ STEL: 30000 ppm

Immediately Dangerous to Life or Health.

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Engineering Measures Local exhaust ventilation to prevent accumulation of high concentrations and maintain air-oxygen

levels at or above 19.5%.

Ventilation Use ventilation adequate to keep exposures below recommended exposure limits.

Personal Protective Equipment

Eye/Face Protection Wear protective eyewear (safety glasses).

Skin and Body Protection Work gloves and safety shoes are recommended when handling cylinders.

Respiratory Protection

General Use No respiratory equipment is needed if workplace oxygen levels are kept above 19.5%.

Emergency Use Use positive pressure airline respirator with escape cylinder or self-contained breathing apparatus

for oxygen-deficient atmospheres (<19.5%).

Hygiene Measures Handle in accordance with good industrial hygiene and safety practices.

9. PHYSICAL AND CHEMICAL PROPERTIES

Product Information

AppearanceColorless.OdorOdorless.Odor ThresholdNo information available.Physical StateCompressed gasFlash PointNot applicable.Autoignition TemperatureNo information available.

Flammability Limits in Air

Upper Not applicable Lower Not applicable

The following information is for the NON-INERT components of this mixture

Chemical Name	Boiling Point	Melting Point	Molecular Weight	Evaporation Rate	WaterSolubility	Vapor Pressure	Vapor Density (Air=1)	Gas Density Kg/m3@20°C
Oxygen	-183°C	-219°C	32.00	-	Slightly soluble	Above critical temperature	1.11	1.33
Carbon dioxide	56°C	-56°C	44.00	-	0.145 g/ml @ 25°C	838 psig (5778 kPa) @ 21.1°C	1.52	1.84

Linde India Limited

Oxygen House, P-43 Taratala Road, Kolkata-700 088

Phone (+91 33) 66021600

The following information is for the INERT components that may be part of this mixture:

Chemical Name	Boiling Point	Melting Point	Molecular	Evaporation Rate	Water Solubility	Vapor Pressure	Vapor Density (Air=1)	Gas Density Kg/m3@20°C
Argon	-185.9°C	-189.4°C	39.94	-	0.056 (vol/vol @ 0°C and 1 atm)	Above critical temperature	1.38	1.65

10. STABILITY AND REACTIVITY

Stability Stable.

Incompatible ProductsCarbon dioxide is incompatible with: Certain reactive metals, hydrides, may ignite. Passing carbon

dioxide over a mixture of sodium peroxide and aluminum or magnesium may explode.

Conditions to Avoid Due to the presence of Carbon dioxide, Carbonic acid is formed in the presence of moisture.

Hazardous Decomposition Products None known based on information supplied.

Hazardous Polymerization Hazardous polymerization does not occur.

11. TOXICOLOGICAL INFORMATION

Information

LD50 Oral: No information available.

LD50 Dermal: No information available.

LC50Inhalation: No information available.

Repeated Dose Toxicity No information available.

Component Information No information available.

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Carbon dioxide			470000 ppm (Rat)

Toxicity

Chronic Toxicity Chronic harmful effects are not known from repeated inhalation of concentrations below PEL/TLV.

Carcinogenicity Contains no ingredient listed as a carcinogen.

Irritation No information available.

Sensitization No information available.

Reproductive Toxicity No information available.

Developmental Toxicity Oxygen deficiency during pregnancy has produced developmental abnormalities in humans and

experimental animals.

Synergistic Materials None known.

Target Organ Effects Central vascular system (CVS). Respiratory system.

Linde India Limited

Oxygen House, P-43 Taratala Road, Kolkata-700 088

Phone (+91 33) 66021600

12. ECOLOGICAL INFORMATION

Ecotoxicity

The environmental impact of this product has not been fully investigated.

Ozone depletion potential; ODP; (R-11 = 1): Does not contain ozone depleting chemical.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods Do not attempt to dispose of residual waste or unused quantities. Return in the shipping container

PROPERLY LABELED WITH ANY VALVE OUTLET PLUGS OR CAPS SECURED AND VALVE PROTECTION CAP IN

PLACE to Linde India Ltd for proper disposal.

Contaminated Packaging Do not re-use empty containers.

14. TRANSPORT INFORMATION

Proper shipping name Compressed gas, n.o.s.

Hazard Class 2.2 Subsidiary Class None UN-Number UN1956

Description UN1956, Compressed gas, n.o.s. (Argon, Carbon Dioxide, Oxygen), 2.2

15. Regulatory Information

Labeling of cylindersLabel 2.2: non-flammable non-toxic gas.Risk phrasesRAs Asphyxiate in high concentrations.Safety phrasesS9 Keep container in a well-ventilated place.

S23 Do not breathe gas.

16. OtherInformation



General Ensure all national/local regulations are observed.

The hazard of asphyxiation is often overlooked and must be stressed during operator training.

Document Information In preparing this document help has been taken from MSDS for Linde (US)

DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s). The information contained in this document only covers the hazards presented by this material, it does not constitute a work place risk assessment.

End of Safety Data Sheet

Linde India Limited Oxygen House, P-43 Taratala Road, Kolkata-700 088 Phone (+91 33) 66021600